

TURBOLITE™ + HOT FLASH KEVLAR® & NOMEX®

The Honeywell Miller Turbolite+ Hot Flash Personal Fall Limiter (PFL) is designed specifically for those who work at height and are exposed to arc flash hazards or high heat areas, such as hot work applications. This PFL helps provide versatility, reliability and maximum safety across any hot work application involving cutting, welding, soldering, grinding, or any similar activity producing a spark, flame, or heat.

The original Personal Fall Limiter is now part of the PLUS family of newly redesigned self-retracting devices (SRDs), rated to provide protection as per OSHA for up to 420lb (190.5 kg) worker, showcasing new user-friendly labels and design that aligns with Honeywell Miller harnesses.

NEW PRODUCT DESIGN



FEATURES AND BENEFITS

- Meets OSHA 1926.502 and Certified ANSI Z359.14-2021 Class 1
- An all-in-one solution for arc flash and hot work applications
- High-impact housing with integral shock absorber
- Rated to provide protection for up to 420lbs (190.5 kg) worker per OSHA
- Meets the most stringent safety standards, including ANSI Z359.14-2021 and ASTM F887
- Features a web lifeline comprised of Kevlar® and Nomex® materials which provides resistance to flame, heat, and burns
- Designed to maintain flame resistance of up to 40±5 cal cm². In addition to providing flame resistance

RECOMMENDED INDUSTRIES/USE

- Utilities
- Construction
- Electricians
- General Industry
- Government
- Ironwork
- Wind Energy

ORDERING INFORMATION

SKU	LENGTH	LIFELINE CONFIGURATION	UNIT CONNECTOR	LIFELINE CONNECTOR	MAX. WORKING CAPACITY	
					ANSI	OSHA
MTL-AFA1-63/4.5FT	4.5FT	Single	Aluminum harness one pin connector	Aluminum captive eye carabiner	310 lb (141 kg)	420 lb (190.5 kg)
MTL-AFA1-67/4.5FT	4.5FT	Single	Aluminum harness one pin connector	Aluminum Locking Snap Hook	310 lb (141 kg)	420 lb (190.5 kg)
MTL-OAF1-61/6FT	6FT	Single	Aluminum harness one pin connector	Steel Locking Snap Hook	310 lb (141 kg)	420 lb (190.5 kg)
MTL-OAF1-63/6FT	6FT	Single	Aluminum harness one pin connector	Aluminum captive eye carabiner	310 lb (141 kg)	420 lb (190.5 kg)
MTL-OAF1-65/6FT	6FT	Single	Aluminum harness one pin connector	Steel Locking Swivel Snap Hook	310 lb (141 kg)	420 lb (190.5 kg)
MTL-OAF1-67/6FT	6FT	Single	Aluminum harness one pin connector	Aluminum Locking Snap Hook	310 lb (141 kg)	420 lb (190.5 kg)
MTL-OAF2-61/6FT	6FT	Twin	Aluminum harness one pin connector	Steel Locking Snap Hook	310 lb (141 kg)	420 lb (190.5 kg)
MTL-OAF2-63/6FT	6FT	Twin	Aluminum harness one pin connector	Aluminum captive eye carabiner	310 lb (141 kg)	420 lb (190.5 kg)
MTL-OAF2-65/6FT	6FT	Twin	Aluminum harness one pin connector	Steel Locking Swivel Snap Hook	310 lb (141 kg)	420 lb (190.5 kg)
MTL-OAF2-67/6FT	6FT	Twin	Aluminum harness one pin connector	Aluminum Locking Snap Hook	310 lb (141 kg)	420 lb (190.5 kg)

For more Information

automation.honeywell.com

For Information on Innovations and Patents

hsmpats.com

Honeywell Safety Products USA, Inc.

855 S Mint St
Charlotte, NC 28202
www.honeywell.com

HPPE_Fall_Turbolite_Hot_Flash_Sell_Sheet | 9/24
©2024 Honeywell International Inc.

