

transnorm
your best move



Reliable and powerful
modules for Intralogistics
Made by TRANSNORM

Global
Excellence for
Intralogistics

Global Excellence for Intralogistics


HIGH-PERFORMANCE MODULES FOR END USERS AND SYSTEM INTEGRATORS



More than 150,000 belt curves in use worldwide.


TRANSNORM is one of the leading global manufacturers of high performance modules for totes, bags, cartons, parcels and flight baggage conveyor systems. With our extensive expertise we safeguard the competitive edge enjoyed by end users and system integrators in various segments of intralogistics – particularly when it comes to high performance distribution demands and problematic loads which need to be conveyed.

With the slogan "Global Excellence for Intralogistics", TRANSNORM meets the demands with respect to quality, reliability and maintenance-friendliness of our modules and solutions all over the world. All of these are aspects that ensure efficient and cost effective system operation. To further strengthen and complement the existing TRANSNORM range, SOVEX vehicle loaders and conveyors offer an agile solution for robust inbound and outbound handling.




BELT CURVE CONVEYORS
Conveys goods in either direction, even at high speeds

- Weight load: up to 250 kg
- Conveyor angle: up to 180°




BELT CONVEYOR
Accurate, high speed handling with smooth starts & stops

- Weight Load: up to 50 kg/m
- Conveyor length: up to 30,000 mm




HELIX BELT CURVES
Reversible direction whilst overcoming level changes

- Nominal width: up to 1,200 mm
- Gradient at inner radius: up to 18°




ANGLED BELT CONVEYOR
Full belt design - reliable and accurate

- Conveyor angle: 30°/45°
- Nominal width: up to 1,000 mm




STRIP BELT CONVEYOR
High speed reversible conveyor

- Conveyor speed: up to 3.0 m/s
- Weight load: up to 75 kg




TIMING CONVEYOR
Compact, accurate and dynamic

- Conveyor speed: up to 2.6 m/s
- Nominal width: up to 1,000 mm




ALIGNMENT CONVEYOR
Reliable alignment, suitable for flat-bottomed or limp goods

- Conveyor speed: up to 2.6 m/s
- Nominal width: up to 1,200 mm




ACCUMULATION ROLLER CONVEYOR
Efficient solution for Low Pressure Accumulation without gaps

- Nominal width: up to 1,000 mm
- Conveyor length: up to 20,000 mm



CENTERING LOADS
Centre parcels gently with high performance

- Conveyor speed: up to 2,6 m/s
- Nominal width: up to 2,000 mm




ROLLERMERGE
Contactless merging with high speed and performance

- Performance: up to 6,000 pcs/h
- Nominal width outfeed: 1,000 mm




SMARTSORT® LINE CROSSING
High performance line crossing, merging or diverting

- Outfeed angle: 45°
- Sorting capacity: up to 6,000 pcs/h




SMARTSORT® LINESPLITTER
Dividing lines reliably with high accuracy and speed

- Line splitting: up to 6,000 pcs/h
- Nominal width: up to 1,000 mm




SMARTSORT® DISTRIBUTION CONVEYOR
High throughput and sorting performance with electrical swivel bars

- Outfeed angle: 30°/45°/90°
- Sorting capacity: up to 6,000 pcs/h




ROLLER FUNCTION CONVEYOR 400V
Leading sorting performance which is both highly configurable and energy-efficient

- Outfeed angle: 30°/45°/90°
- Sorting capacity: up to 6,000 pcs/h



ELECTRICAL LIFT-UP ROLLER TRANSFER
A powerful and economical standard module

- Weight load: up to 50 kg
- Outfeed performance: up to 1,800 pcs/h




ROLLER FUNCTION CONVEYOR 24V
Flexible and efficient sorting solution for Intralogistics

- Conveyor speed: up to 1.5 m/s
- Sorting capacity: up to 1,800 pcs/h




VERTISWITCH®
Standardised, dynamic vertical distribution unit

- Weight load: up to 75 kg
- Distribution capacity: up to 1,800 pcs/h




BELT VEHICLE LOADER
Load and unload vehicles at the loading bay or raised dock

- Closed length: min. 6,000 mm
- Extension length: up to 20,000 mm



BENDY BOOM VEHICLE LOADER
Load/unload vans, lorries, trailers & containers using the same equipment & loading bay

- Closed length: min. 6,000 mm
- Extension length: up to 16,700 mm



ROLLER VEHICLE LOADER
A simple, fast, efficient and cost effective loading solution

- Transportation speed: Gravity
- Extension length: up to 15,000 mm

transnorm
your best move



www.transnorm.com