

HALL-EFFECT THEORY AS APPLIED TO ROTARY POSITION SENSORS

Hall-effect sensors are advantageous for use in harsh environments and space-constrained applications.

They have fewer cost limitations, excel in low power requirement operations, and offer simpler installation.

They provide a reliable, low-maintenance solution for many rotary position sensing applications.

TABLE OF CONTENTS

| | |
|-----------|--|
| 3 | What is the Hall Effect |
| 3 | Principle of the Hall Effect |
| 4 | Applications of Hall-effect Technology |
| 4 | Advantages of Hall-effect Devices |
| 5 | Who first discovered the Hall-effect Principle |
| 5 | Edwin Hall's Experimentation |
| 5 | Impact on Science and Technology |
| 5 | Applications of Hall-effect Technology |
| 5 | Hall-effect Sensors |
| 6 | Current Sensing |
| 6 | Transportation Applications |
| 6 | Industrial Applications |
| 6 | Conveyor Systems |
| 6 | Medical Applications |
| 7 | Aerospace |
| 8 | Measuring Rotary Position |
| 8 | Working Principle |
| 8 | Applications of Hall-effect Sensors in Rotary Position Monitoring |
| 9 | Advantages of Using Hall-effect Sensors for Rotary Position Monitoring |
| 10 | Hall-effect Sensors and Optical Encoders |
| 10 | Working Principle |
| 10 | Accuracy and Resolution |
| 10 | Environmental Resistance |
| 11 | Size and Complexity |
| 11 | Power Consumption |
| 11 | Cost |
| 11 | Applications |
| 12 | Choosing between Hall-effect sensors and Optical Encoders |

WHAT IS THE HALL EFFECT

The Hall Effect is a phenomenon observed in physics, particularly in electromagnetism. The Hall-effect principle can be widely utilized in various applications including sensors and measurement devices.

Discovered by Edwin Hall in 1879, the basics and principles of the technology are detailed in this White Paper.

PRINCIPLE OF THE HALL EFFECT

The Hall Effect occurs in a conductor or semiconductor when a magnetic field is applied perpendicular to the flow of electric current. This interaction results in the generation of a voltage difference, known as the Hall voltage, across the material, perpendicular to both the current direction and the magnetic field.

- 1. Current Flow:** When an electric current passes through a conductor, it results in the movement of charge carriers (such as electrons in metals or holes in semiconductors) within the material.
- 2. Magnetic Field Interaction:** When a magnetic field is applied perpendicular to the direction of the current flow, the moving charge carriers experience a force, the Lorentz force that acts at right angles to their direction of motion and the magnetic field.
- 3. Charge Accumulation:** As a result of this force, charge carriers are deflected to one side of the conductor, causing one side to be positively charged and the opposite side to be negatively charged. This separation of charge creates an electric field across the material.
- 4. Hall Voltage Generation:** The difference in electric charge leads to the establishment of a voltage across the conductor, known as Hall voltage. The magnitude of this voltage is proportional to the strength of the magnetic field and the amount of current flowing through the conductor.

Figure 1. Industrial Robotics



APPLICATIONS OF HALL-EFFECT TECHNOLOGY

- 1. Hall-effect Sensors:** These sensors are commonly used to measure magnetic field strength. They are widely deployed in various devices such as:
 - Proximity sensors
 - Position sensors
 - Speed and angle measurement sensors
- 2. Current Sensing:** Hall-effect technology allows for non-intrusive current measurement. By placing a Hall sensor near a current-carrying conductor, the magnetic field generated by the current can be measured without direct electrical connections.
- 3. Automotive Applications:** Hall-effect sensors are utilized in various automotive systems for determining the position of the crankshaft in an engine or controlling the operation of electric motors.
- 4. Electronics:** These sensors are used in electronic circuits to detect the presence of magnetic fields and can be found in compasses and flow meters.

ADVANTAGES OF HALL-EFFECT DEVICES

- **Non-Contact Measurement:** Hall-effect sensors can measure magnetic fields without needing physical contact with the conductive material
- **Robustness:** They are usually less sensitive to environmental factors and represent a reliable solution in harsh working conditions
- **Wide Range:** Hall-effect sensors can operate over various temperatures and in various fields, making them adaptable to numerous applications

SUMMARY

Hall-effect technology is pivotal in the measurement and sensing of magnetic fields, providing essential functionality in electronics, automotive, and industrial applications. Its reliability and non-contact measurement capability make it an invaluable tool in modern technology.

DISCOVERY OF THE HALL-EFFECT PRINCIPLE

The Hall-effect principle was discovered by American physicist Edwin Hall in 1879. While conducting experiments in a laboratory, Hall observed that when an electric current flowed through a conductor in the presence of a magnetic field, a voltage generated was perpendicular to both the current and the magnetic field.

EDWIN HALL'S EXPERIMENTATION

- **Setup:** Hall's initial experiments involved a thin gold foil containing a small electric current and a magnetic field applied perpendicularly to the current flow.
- **Observation:** He noted that a voltage difference appeared across the foil—the Hall voltage—deflecting charge carriers to one side of the conductor due to the magnetic field.
- **Significance:** This finding laid the foundation for understanding the behavior of charged particles in magnetic fields and contributed to the field of physics, particularly electromagnetism and semiconductor technology.

IMPACT ON SCIENCE AND TECHNOLOGY

Edwin Hall's discovery of the Hall Effect has been applied extensively across various fields. It has led to the development of Hall-effect sensors that are commonly used in automobiles, consumer electronics, and industrial applications for current sensing, position detection, and magnetic field measurement.

The Hall Effect has not only enabled practical advancements in technology but has also contributed to a deeper understanding of solid-state physics and the properties of materials.

APPLICATIONS OF HALL-EFFECT TECHNOLOGY

Hall-effect technology has many practical uses across various industries due to its ability to measure magnetic fields and electric currents without physical contact. Some applications include:

1. Hall-effect Sensors

A. Position Sensing

Hall-effect sensors are widely used to determine the position of components in machinery. In robotics and automation, these sensors can confirm the position of moving parts, contributing to precise control.

B. Proximity Sensors

These sensors can detect the presence of nearby magnetic objects, making them valuable in applications such as door position sensing in security systems, and as device switches.

C. Rotational Position Sensing

Hall-effect sensors can measure the angle of rotation of a shaft. This is crucial in automotive applications for the detection of crankshaft and camshaft position.

2. Current Sensing

A. Non-Invasive Current Measurement

Hall-effect technology allows for the measurement of current without interrupting the circuit. This non-invasive characteristic makes it ideal for:

- Electric vehicle battery monitoring
- Power distribution equipment for monitoring current loads
- Industrial equipment for monitoring motors and other devices

B. Smart Power Management

In energy management systems, Hall-effect sensors help monitor energy consumption in real-time, allowing for better energy efficiency and management.

3. Transportation Applications

A. Speed Sensors

In automotive engineering, Hall-effect sensors are used for encoding wheel speed data and monitoring vehicle speed. This data is integral for systems such as anti-lock braking systems (ABS) and traction control systems.

B. Electronic Throttle Control

Hall-effect technology enables the measurement of throttle position, which assists in optimizing engine performance and fuel efficiency by adjusting the air intake to the engine.

C. Fuel Level Sensors

Hall-effect sensors can be utilized in fuel tanks to accurately measure fuel levels, providing feedback to the vehicle's fuel gauge.

4. Industrial Applications

A. Robotics and Automation

Hall-effect sensors are often used in industrial robots for feedback in position and motion control, facilitating precision in automated tasks.

5. Conveyor Systems

In manufacturing, these sensors can monitor the position of items on conveyor belts, ensuring correct positioning for further processing.

6. Medical Applications

A. Medical Equipment

In healthcare, Hall-effect sensors monitor mechanical arms in robotic surgeries or detect the position of multiple axes in imaging equipment to maximize operational capabilities.

Figure 2. Robotics and Automation



Figure 3. Conveyor Systems



Figure 4. Medical Equipment



Figure 5. Navigation and Control System in Aircraft



7. Aerospace

In the aerospace industry, Hall-effect sensors are used for navigation and control systems in aircraft, enabling accurate measurements in environments where traditional methods might fail.

SUMMARY

Hall-effect technology's versatility and reliability make it a preferred choice in numerous applications across diverse industries. Its ability to provide precise, non-contact measurements enhances both functionality and safety in the devices and systems that utilize it.

MEASURING ROTARY POSITION

Hall-effect sensors are widely utilized to monitor rotary positions in various applications due to their precision, reliability, and non-contact measurement capabilities. Here's how Hall-effect sensors can be deployed for monitoring rotary position:

WORKING PRINCIPLE

- 1. Magnetic Field Generation:** In rotary position sensing, Hall-effect sensors typically work in conjunction with a rotating magnetic disk or a magnet fixed to a rotating object (like a motor shaft). These arrangements utilize permanent magnets or magnetic encoders that can produce a magnetic field around the sensor.
- 2. Detection of Magnetic Poles:** As the magnetic disk or magnet rotates, the Hall-effect sensor detects the changes in the magnetic field strength as the magnetic poles (north and south) pass by the sensor. The sensor generates a voltage signal when it detects a magnetic field, and this signal is proportional to the field strength.
- 3. Output Signal Generation:** The Hall-effect sensor produces output signals in the form of pulses as it detects each magnetic pole. The frequency and pattern of these pulses correspond to the angular position and rotational speed of the object.
- 4. Rotary Position Calculation:** The system typically converts the pulse signals into angular position data using a microcontroller or a digital signal processor (DSP). The angle of rotation can be calculated based on the number of pulses and the known characteristics of the rotary system (like the number of poles on the disk):

$$\text{Angle} = \left(\frac{\text{Number of Pulses}}{\text{Pulses per Revolution}} \right) \times 360^\circ$$

APPLICATIONS OF HALL-EFFECT SENSORS IN ROTARY POSITION MONITORING


1. Motor Control:

- **Brushless dc Motors:** Hall-effect sensors are commonly used in brushless dc motors to determine rotor position. This information is essential for controlling the timing of the electrical phases supplied to the motor, allowing for efficient operation and speed control
- **Servo Motors:** They are also utilized in servo motors for feedback on angular position, ensuring precise control in applications like robotics and CNC machinery

2. Automotive Applications:

- **Throttle Position Sensors:** Hall-effect sensors are employed to measure the position of the throttle plate, providing input to the engine control unit for optimal fuel injection and air mixture, enhancing engine performance

Figure 6. Motor Control



- **Steering Angle Sensors:** These sensors detect the angle of the steering wheel, crucial for stability control systems and assistive steering technologies in modern vehicles

3. Industrial Machinery:

- In industrial automation, Hall-effect sensors can monitor the position of robotic arms or conveyor systems. This feedback is integral for precise movement and safety in manufacturing processes

4. Position Encoders:

- Incremental and absolute encoders frequently utilize Hall-effect technology for positional feedback. They are applied in various industries, such as automation, manufacturing, medical, and aerospace, where precise position detection is critical

5. Home Appliances:

- Hall-effect sensors can also be found in appliances, such as washing machines and dishwashers, where they help determine the rotational position of agitators, motors, and other components for optimal performance

ADVANTAGES OF USING HALL-EFFECT SENSORS FOR ROTARY POSITION MONITORING

- **Non-Contact Measurement:** The sensors do not require physical contact with moving parts, reducing wear and tear and promoting a longer lifespan
- **High Reliability:** Hall-effect sensors are robust and resistant to dust, dirt, and moisture, making them effective in diverse environmental conditions
- **Precision:** These sensors deliver high accuracy in position detection, which is crucial for applications that require precise movements
- **Cost-Effective:** Hall-effect technology often offers a cost-effective solution for rotary position sensing compared to other technologies, such as optical encoders

SUMMARY

Hall-effect sensors are an excellent choice for monitoring rotary position due to their reliability, accuracy, and ability to function in harsh conditions. They are used across various industries and applications, ensuring precise control over both speed and position in mechanical systems.

HALL-EFFECT SENSORS AND OPTICAL ENCODERS

Hall-effect sensors and optical encoders are both commonly used technologies for rotary position sensing, but they operate on different principles and have distinct characteristics, advantages, and limitations.

A detailed comparison of Hall-effect sensors and optical encoders in relation to their effectiveness and deployment in rotary position sensing:

WORKING PRINCIPLE

Hall-effect Sensors

Hall-effect sensors work by detecting changes in magnetic fields. They typically use a magnet or magnetic encoder that generates a magnetic field, which is sensed by the rotating Hall-effect sensor. The sensor outputs a voltage proportional to the magnetic field, allowing the measurement of angular position based on the detected magnetic poles.

Optical Encoders

Optical encoders function by using light and optical sensors (like photodiodes). In these encoders, a light source (LED) shines on a coded disk with alternately opaque and transparent segments. As the disk rotates, the light beam is interrupted or transmitted through the segments, generating pulses that correspond to the position of the disk. The resulting signals are processed to determine the angular position.

ACCURACY AND RESOLUTION

Hall-effect Sensors

While Hall-effect sensors provide good accuracy, their resolution is typically limited by the number of magnetic poles used. The resolution can be affected by factors such as the distance between the magnet and the sensor. Accordingly, the resolution may not be as high as optical encoders for applications requiring fine precision.

Optical Encoders

Optical encoders generally offer higher resolution and accuracy since the pulses generated can be very fine, depending on the number of slots on the encoder disk. They can achieve resolutions in the thousands of counts per revolution, making them suitable for high-precision applications.

ENVIRONMENTAL RESISTANCE

Hall-effect Sensors

Hall-effect sensors are known for their robustness and resistance to environmental factors such as dust, dirt, and moisture. They can perform well in harsh conditions, making them ideal for industrial applications.



RTY Hall-effect Sensor



RTY Dual-Output Hall-effect Sensor

Optical Encoders

Optical encoders, on the other hand, are more susceptible to contamination. Dust or debris on the encoder disk can interfere with light transmission, leading to erroneous readings. They may require more frequent maintenance in dirty environments.

SIZE AND COMPLEXITY

Hall-effect Sensors

Hall-effect sensors are generally simpler and more compact compared to optical encoders. They can be easily integrated into various applications, making them ideal for smaller devices.

Optical Encoders

Optical encoders tend to be more complex, as they require additional components such as light sources and photodetectors. This complexity can lead to larger sizes and more intricate mounting requirements.

POWER CONSUMPTION

Hall-effect Sensors

Hall-effect sensors typically consume less power, making them suitable for battery-operated and low-power applications.

Optical Encoders

Optical encoders may consume more power depending on the type of light source used. However, modern encoders can also be designed to be energy-efficient.

COST

Hall-effect Sensors

Generally, Hall-effect sensors are more cost-effective. Their simplicity in design and manufacturing results in lower costs, making them a suitable choice for many applications.

Optical Encoders

Optical encoders can be more expensive due to their complexity and level of precision. For high-resolution types, the cost can significantly increase.

APPLICATIONS

Hall-effect Sensors

Used in various applications including automotive systems (e.g., throttle position, wheel speed), industrial robotics, and consumer electronics.

Optical Encoders

Commonly used in applications requiring high precision, such as CNC machinery, robotics, and aerospace applications.

CONCLUSION

Both Hall-effect sensors and optical encoders serve specific niches within rotary position sensing applications. The choice between the two technologies will depend on factors such as required precision, environmental conditions, space constraints, budget, and application requirements.

CHOOSING BETWEEN HALL-EFFECT SENSORS AND OPTICAL ENCODERS

Choosing between Hall-effect sensors and optical encoders for rotary position sensing involves considering specific conditions and application requirements.

When deciding between Hall-effect sensors and optical encoders, these considerations should be thoroughly evaluated.

1. Harsh Environmental Conditions

- **Dusty or Dirty Environments:** In settings where there is significant dust, dirt, or moisture, Hall-effect sensors are preferred. They are robust and can operate effectively without the risk of contamination affecting their performance, unlike optical encoders, that can malfunction if dirt obstructs the light path
- **Extreme Temperatures:** Hall-effect sensors can typically operate in a broader range of temperatures. If an application requires operation in extreme heat or cold, Hall-effect sensors are often more suitable due to their durability and reliability

2. Compact and Simple Design Requirements

- **Size Constraints:** In applications where space is limited, Hall-effect sensors are more compact and have simpler designs. Their small footprint makes them ideal for integration into tight spaces, such as in microcontrollers, small motors, or portable devices
- **Simpler Installation:** Hall-effect sensors often require less complex installation compared to optical encoders. Their straightforward mounting and wiring can reduce the overall system setup time and effort

3. Cost Considerations

- **Budget Constraints:** Hall-effect sensors are generally more cost-effective than optical encoders. If a project has limited funding or requires a large number of sensors, opting for Hall-effect technology can significantly reduce overall costs
- **Economical Solutions for Lower Precision:** In applications where high precision is not critical, Hall-effect sensors can provide sufficient performance at a lower cost compared to optical encoders that provide higher resolution but may be unnecessary for less critical applications

4. Non-Contact Measurement Benefits

- **Wear and Tear Concerns:** Hall-effect sensors provide a non-contact solution for rotary position sensing. If the system involves rotating parts that undergo significant wear, using Hall-effect sensors can help extend the lifespan of the components by eliminating the need for physical contact

5. Power Consumption

- **Low-Power Applications:** Hall-effect sensors consume less power, making them ideal for battery-operated devices or systems where energy efficiency is a priority. If the application requires long battery life or low power consumption, Hall-effect sensors are a better fit

6. Simplicity in Signal Processing

- **Basic Position Feedback Needs:** If the application requires basic rotational position feedback without the complexity of high-resolution data logging or intricate processing, Hall-effect sensors can fulfill these requirements efficiently. The straightforward output signal allows for easy integration with simple control systems

7. Direct Measurements of Magnetic Fields

- **For Magnetic Applications:** In scenarios where the monitored object is a magnetic material or has magnets integrated (e.g., certain brushless dc motors, positioning systems), Hall-effect sensors can directly measure the magnetic field and provide accurate position feedback, potentially simplifying the design

8. Automotive and Industrial Applications

- **Automotive Applications:** In automotive systems such as crankshaft or camshaft position measurement, Hall-effect sensors are commonly used due to their robustness and reliability, providing accurate sensing in dynamic conditions
- **Direct Drive Systems:** For direct drive applications in robotics or industrial machinery, where the system might experience frequent starts and stops, Hall-effect sensors can offer reliable position detection without mechanical alignment issues commonly associated with optical systems

CONCLUSION

Hall-effect sensors are particularly advantageous in conditions characterized by harsh environments, space constraints, cost limitations, low power requirements, and simpler installation. They provide a reliable, low-maintenance solution for many rotary position sensing applications.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgment or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.

While Honeywell may provide information or engineering support for its products through Honeywell personnel, literature and website, it is the buyer's sole responsibility to determine the suitability of the Honeywell product(s) for the buyer's requirements.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this writing. However, Honeywell assumes no responsibility for its use.

For more information

Honeywell Sensing Solutions services its customers through a worldwide network of sales offices and distributors.

For application assistance, current specifications, pricing or the nearest Authorized Distributor, visit [our website](#) or call:

| | |
|---------------|---------------------|
| USA/Canada | +1 302 613 4491 |
| Latin America | +1 305 805 8188 |
| Europe | +44 1344 238258 |
| Japan | +81 (0) 3-6730-7152 |
| Singapore | +65 6355 2828 |
| Greater China | +86 4006396841 |

Honeywell Sensing Solutions

830 East Arapaho Road
Richardson, TX 75081
www.honeywell.com